

Induction warming system IWS650



Description

With the "invisible" induction warming system, the worktop can be used either as a warming area or work surface. Installed under a worktop, the impressive technology allows a chafing dish to be heated up to 100 °C while the worktop temperature reaches a maximum of 35 °C.

Features

Number of warming stations:	1
Material:	Stainless steel
 Type of warming station(s): 	Induction
Important information:	-
Suitable worktop material:	1/1 GN
·	2/3 GN
	Round up to 40 cm
	Glass
	Ceramic
	Marble
	Quartz
	Stone
 Suitable worktop thickness: 	4 - 20 mm
 Maximum worktop temperature: 	35 °C
Regulation of:	Output
Output max.:	650 W
• Temperature range induction warming system:	to 55 °C







- Induction warming system for more flexibility
 - Installation below the worktop
 - Worktop can be used either as a warming station or work surface



- Temperature range induction warming system: up to 55 °C
- Temperature range chafing dish: up to 100 °C



- Spacer
 - ✓ For optimal heat transfer without heating the work surface
 - ✓ Maximum worktop temperature: 35 °C

Suitable worktop material:

- 🗸 Glass
- 🗸 Ceramic
- 🗸 Marble
- 🗸 Quartz
- 🗸 Stone



Induction warming system IWS650

Up to 100 °C

20

•	Temperature	range	chafing	dish:
---	-------------	-------	---------	-------

- Number of output levels:Control panel:
- Pot recognition:
- Lock button (child protection):
- Timer:
- Digital display:
- Overheating protection:
 ON/OFF switch:
- CON/OFF switch:
 Control lamp:
- Control unit:
- Equipment connection:
- Properties: Including:
- Power load:
- Not included in delivery:
- Size:
- Weight:

Cable length: 2 m Separate Yes No No Yes Yes Yes Electronic Touch Pluggable Washable air filter 1 spacer 0,65 kW | 230 V | 50 Hz Chafing dish W 340 x D 340 x H 175 mm 4.9 kg







Induction warming system IWS650 Add on Products

