

Drawer chiller 600S2



Number of drawers: 2 Maximum bottle height: Top 275 mm Bottom 275 mm



Load-bearing capacity per drawer: 20 kg



Top drawer has perforated base

Description

This drawer chiller has 2 drawers and can be integrated with other units, making it ideal for installation between cabinets in cafés and bars. The circulation cooling and perforated base of the top drawer ensure even temperature distribution.

Features

Load-bearing capacity of each drawer, max:	20 kg
Number of drawers:	2
Material:	Stainless steel
Max. bottle height:	275 mm
Important information:	
Drawer dimensions:	Bottom: W 440 x D 250 mm
	Top: W 440 x D 440 mm
 Norm-format drawers: 	-
Temperature range:	0 °C to 10 °C
Thermostat:	Yes
Temperature control:	In 1 °C steps
Can be installed:	Yes
Cooling:	Circulating air
Climate class:	4
Coolant:	R290 / 0,040 kg
 Energy efficiency class: 	D (EU Nr. 2015 / 1094)
Energy consumption:	1095 kWh / an

Continue on the next page



Code-No. **110159** GTIN 4015613719450



Drawer chiller 600S2

- Drip water evaporation:
- Digital display:Control unit:
- ON/OFF switch:
- Control lamp:
- Delivery state:
- Properties:
- Including:
- Not included in delivery:Power load:
- Size:
- Weight:

Yes Yes Electronic No

> Permanently mounted Top drawer has perforated base

0,167 kW | 230 V | 50 Hz W 600 x D 645 x H 845 mm 50.8 kg







Drawer chiller 600S2 Add on Products

