



▶ Extractor hood for wall mounting

▶ Design

✓ Depth: 700 mm

✓ Width: 1,000 mm

▶ Max. air throughput: 880 m³/h


▶ 2 flame protection filters

✓ Type A



▶ LED lighting

✓ 1 x 8 W



▶ Welded-on grease collection channel with discharge tap



This extractor hood with a maximum air throughput of 880 m³/h is fitted with 2 filters and is intended for wall mounting. The LED lighting ensures a well-lit working area around your cooker, griddle, and so on.

- Operating mode: Exhaust air
- Assembly type: Wall
- Max. air throughput: 880 m³/h
- Flame protection filter: Type A
- Number of filters: 2
- Material filter: Stainless steel
- Protection class: IP54
- Lighting: LED
- Lamps (number + watt): 1 x 8 W
- Available on request: Other sizes
- Including: -
- Power load: 0,008 kW | 230 V | 50-60 Hz
- Material: Stainless steel
- Important information: -
- Properties: Filter carrier
- Size: W 1,000 x D 700 x H 450 mm
- Weight: 29 kg

Extractor hood 700-W1000

Add on Products

Intensive power cleaner F1L, set of 2



- Order quantity unit: 1 box (2 bottles)
- Content: 2 x 1 litre
- Ph level: 14
- HACCP compliant: Yes
- Chlorine-free: Yes
- Phosphate-free: Yes
- Including: 1 spray head
1 spray lance
- Important information: Attention: Not suitable for surfaces sensitive to alkali such aluminium
Exclusively available in Germany and Austria

Code-No. 173080
GTIN 4015613731933