



401.619

Bedienungsanleitung
Handwaschbecken mit Knie-Bedienung

D/A/CH

Instruction manual
Knee-operated hand wash basin

GB/UK

Mode d'emploi
Lave-mains avec commande au genou

F/B/CH

Manuale di utilizzo
Lavamani azionato a ginocchio

I/CH

Mantenga las instrucciones
Lavamanos con accionamiento por rodilla

E

Manual de instruções
Lavatório operacional com o joelho

P

Bedieningshandleiding
Handwasbak met kniebediening

NL/B

Brugsanvisning skal
Håndvask med knæbetjening

DK

Инструкция по эксплуатации
Умывальник с коленным включением

RUS

Kullanma kılavuzu
Diz idareli el yıkama lavabosu

TR

Instrukcja obsługi
Umywalka z włącznikiem kolanowym

PL

Návod k obsluze
Umyvadlo s obsluhou pomocí kolena

CZ

Upute za upotrebu
Umivaonik s upravljanjem koljenom

HR

Használati útmutató
Falra szerelhető térdkapcsolós mosdókagyló

H

Οι οδηγίες χρήσης που ακολουθούν
νιπτήρας χεριών με διακόπτη γονάτου

GR

Technical information:

Name:	• Knee-operated hand wash basin
Article number:	• 401.619
Construction:	• stainless steel
Dimensions:	• W 400 x D 400 x H 345 mm height including tap 510 mm basin Ø 350 mm
Weight:	• 8.65 kg
Equipment:	• swiveling tap 200 mm, siphon Ø 40 mm

Assembly

- Unpack the unit and remove its packaging.
- Check that all elements are present:
 - basin;
 - plug;
 - swiveling tap;
 - siphon.
- Hang the basin near a water connection.
- Before mounting the basin, check to ensure that the wall on which the basin will be mounted can support its weight.
- Install the swiveling tap in the basin, at the place indicated in figure 1.




Fig. 1

- Drill two holes in the wall.
- Leave a space of 280 mm between the holes, as shown in figure 2.
- Insert the dowels and screws included with the unit into the drilled holes and hang the basin on them.




Fig. 2

- Connect the basin to the water supply using the included assembly kit. The basin may be connected to either hot or cold water, or both.
- Connect the basin to a drain pipe.
- The basin is activated by pressing the plate at the front with one's knee (fig. 3).
- Water will flow from the tap for approx. 15 seconds. After this time the flow will automatically shut off.




Fig. 3

- The proportion of hot and cold water is controlled using the regulating screw (fig. 4).

Washing

- Wash the basin regularly using a soft cloth and non-abrasive cleaning substance.




Fig. 4

Bartscher GmbH
Franz-Kleine-Str. 28
D-33154 Salzkotten
Germany

phone: +49 (0) 5258 971-0
fax: +49 (0) 5258 971-120