

Cooling top unit SushiBar GL2-180



- ▶ For 5 x 1/2 GN to 40 mm deep
- ▶ Static cooling with additional evaporator tube on top
- ▶ Energy-saving LED lights that can be switched separately



- ▶ Back with glass sliding doors for easy loading
- ▶ GN container not included in the delivery

Description

For ideal presentation of your food - e.g. sushi or tapas. The high-performance refrigerated showcase stands out thanks to its functionality and design

Features

- | | |
|----------------------------|-----------------------------------|
| • Front pane: | Rounded |
| • Power load: | 0,18 kW 230 V 50 Hz |
| • Material: | CNS 18/10 |
| | Plastic |
| | Glass |
| • Including: | 1 bar: length 325 mm, width 30 mm |
| • Important information: | - |
| • Safety glass: | Yes |
| • Type of glass: | Single glazing |
| • Temperature range: | 2 °C to 7 °C |
| • Colour: | Silver |
| • Energy efficiency class: | C (EU No. 2019 / 2024) |
| • Control unit: | Electronic |
| | Knob |
| • Energy consumption: | 1075 kWh / an |
| • Control lamp: | Defrost |
| • Temperature control: | Digital |

▶ Continue on the next page



Cooling top unit SushiBar GL2-180

- Climate class: 4
- Cooling: Static
- Coolant: R600a / 0,095 kg
- Digital display: Yes
- Lighting: LED
Can be switched separately
- Delivery state: Permanently mounted
- Depth GN container max.: 40 mm
- Automatic defrosting function: Yes
- Drip water evaporation: Yes
- ON/OFF switch: Yes
- Capacity GN: 5 x 1/2 GN
- Properties: Back with glass sliding doors
With additional evaporator tube on top
- Design: Closed glass casing
- Not included in delivery: GN containers
- Size: W 1,800 x D 425 x H 295 mm
- Weight: 45.1 kg

