


Dishwasher Deltamat TF 516 LPWR



- ▶ With lye pump, water softener and cleaning agent dosing pump



- ▶ Output/h: 40 baskets
- ▶ Run-time: 90 / 120 / 180 seconds



- ▶ Double-walled door
- ▶ Can be fitted below the counter
- ▶ We recommend a warm water connection up to 55 °C

Description



Features

• Plate height max.:	345 mm
• Door double-walled:	Yes
• Can be fitted below the counter:	Yes
• Glasses height max.:	320 mm
• Power load:	5,15 kW 400 V 50 Hz
• Equipment connection:	3 NAC
• Boiler heater:	4,5 kW
• Tank heater:	2,7 kW
• Water outlet:	Ø 50 mm
• Dry-run protection:	Yes
• ON/OFF switch:	Yes
• Lye pump:	Yes
• Water softener:	Yes
• Clear rinsing dosing pump:	Yes
• Door contact switch:	Yes
• Cleaning agent dosing pump:	Yes
• Basket dimensions:	500 x 500 mm

▶ Continue on the next page

Dishwasher Deltamat TF 516 LPWR

- Run-time: 90 / 120 / 180 seconds
- Output / hour max.: 40 baskets
- Cold rinsing: No
- Double-walled: No
- Tank volume: 29 litre(s)
- Water pressure: 2 - 4 bar
- Water supply: G 3/4" M
- Material: CNS 18/10
- Water consumption at 2 bar: 2.3 litres / wash cycle
- Size: W 595 x D 630 x H 845 mm
- Weight: 63 kg

