

Refrigerated counter S2T2-150 MA



Description

Features

- | | |
|----------------------------|--------------------------|
| • Number of drawers: | 2 |
| • Type of door: | Leaf door(s) |
| • Number of doors: | 2 |
| • Number of cupboards: | 2 |
| • Cupboards refrigerated: | Yes |
| • Drawers refrigerated: | Yes |
| • Norm-format drawers: | 1/1 GN |
| • Power load: | 0,452 kW 230 V 50 Hz |
| • Height-adjustable feet: | Yes |
| • Temperature range: | 0 °C to 10 °C |
| • Height adjustable: | 850 mm to 900 mm |
| • Tilting: | 50 mm |
| • Cooling: | Circulating air |
| • Coolant: | R134a |
| • Digital display: | Yes |
| • Depth GN container max.: | 150 mm |
| • ON/OFF switch: | Yes |

► Continue on the next page

Refrigerated counter S2T2-150 MA

- Important information: -
- Climate class: 4
- Available on request: Refrigerated counter with glass-doors
Refrigerated counter with swivel castors
- Size drawer: W 299 x D 572 x H 190 mm
- Door hinge side can be changed: Yes
- Size Cupboard: W 335 x D 570 x H 554 mm
- Number of drawers: 1
- Temperature control: Thermostatic
- Control unit: Knob
- Control lamp: ON/OFF
- Drip water evaporation: Yes
- Thermostat: Yes
- Material work surface: Chrome-nickel steel
- Material: Chrome-nickel steel
- Door hinge side: Left / right
- Energy efficiency class: C (EU No. 2015 / 1094)
- Including: 2 grilles (W 325 x D 530 x H 10 mm)
- Size: W 1,792 x D 700 x H 850 mm
- Weight: 123.2 kg



Refrigerated counter S2T2-150 MA

Add on Products

Stainl.steel polish.spray 500ml can



- Content / can: 500 ml
- Application: Remove heavy soiling such as grease residue first
Do not spray onto hot surfaces
- allow them to cool down first:
- Application: Before use, bring the can to room temperature and shake well

Code-No. 173031
GTIN 4015613360195