

## Thermometer D3000 KTP-KL



# Temperature range: -40 °C to 300 °C -58 °F to 572 °F



### Digital design

- Measurement cycle: 3-4 seconds
- Min./max. memory
- Display illuminated



- With core temperature sensor
  Puncture depth: 110 mm
  - ranetale deptil. Fro him
  - Fold-away temperature sensor

# Description

Watertight thermometer with fold-away core temperature sensor. The large temperature measuring range from -40°C to +300°C is just as convincing as the illuminated display and the min./ max. memory.

Electronic

### Features

### • Control unit:

- Puncture depth:
- Temperature range:
- Design:
- With temperature sensor:
- Colour:
- Temperature measurement units:
- Material temperature sensor:
- Diameter temperature sensor:
- Material:
- Size of display field:
- Protection class:
- Properties:

110 mm -40 °C to 300 °C Digital Yes White °C °F Stainless steel 3,5 mm Plastic ABS W 48 x H 16.7 mm IP68 Fold-away temperature sensor Display illuminated Min./max. memory Automatic shutdown after 60 minutes

### • Continue on the next page





# Thermometer D3000 KTP-KL

### • Properties:

- Important information:
- Including:
- Battery:Application area:
- Designed for: Size:
- Weight:

Measurement cycle: 3-4 seconds Watertight Temperature range also in Fahrenheit Do not use in oven 2 batteries Button cell CR2032 Steaming Cooling Core temperature measurements W 155 x D 45 x H 23 mm 0.09 kg



